

# **Eskom- New coal units and suggestions for further improvement**

EPRI Workshop on Advanced  
Cooling Technologies, 9 July 2008

Francois du Preez

# Content

- **New coal units**
- **Interaction of ACC platforms**
- **CFD simulation of new ACC**
- **Main design characteristics of new ACC**
- **Future design trends**
- **Suggestions for further work**
- **Conclusion**
- **Acknowledgment**
- **References**

# New coal units


- Detailed investigations into new coal fired capacity started in 2004.
- Fuel sourced from the same mine which supplies Matimba
- Only dry cooling was considered due to limited water in area
  - Mean annual rainfall is 470 mm (18.5")
- A life cycle cost comparison was done between the two known dry cooling technologies in South Africa
  - Indirect type (Kendal)
  - Direct type (Matimba)
- Based on available information at the time, direct dry cooling was selected

# Medupi, 6 x 794 MW


- First supercritical hard coal fired units to be build in South Africa
- Turbine steam conditions: 24.1 MPa/560°C/570 °C  
3495 psi/1040°F/1058°F
- Coal supplied from the same coal mine as Matimba therefore the two stations are located relative close to each other, 6 km (3.7 miles).
- Boiler and turbine contracts awarded in 2007
- ACC included in turbine contract
- **Questions to be answered:**
  - Will the two ACC's affect each other?
  - How to change the ACC enquiry to prevent similar problems experienced at Matimba?
- Initiate a CFD study to investigate various alternatives

# Simulation results of 2 adjacent ACC's 6 km apart

No plume or pressure field interaction was found



Temperature  
contour plots,  
scale 20 - 21°C



# CFD analysis of ACC performance during windy conditions


- **Full numerical analysis of a single axial flow fan**
- **Stage 1: “Test section” conditions**
  - Characterize fan performance numerically in test section conditions
  - Predicted performance characteristics compared to that supplied by fan vendor
- **Stage 2: Fan in A-frame**
  - Full numerical analysis of a single axial flow fan in A-frame
  - Characterize fan performance during normal inlet flow (no wind) conditions with inlet and outlet obstructions including heat exchangers
  - Characterize fan performance with distorted inlet flow conditions
  - Quantify fluctuating forces and bending moments on individual fan blades for fans subject to distorted inlet flow conditions
    - Fan performance correlations obtained by full numerical analysis used in ACC simulation (multiple fans)

# CFD analysis of ACC performance during windy conditions cont.


- Study performed for representative ACC (Matimba)
- Include boiler structure and turbine house
- ACC performance determined steady state conditions
- Performance evaluated for different wind directions
- 2 Wind speeds: zero and 9 m/s at 40 m Above Ground Level
- One representative air inlet temperature
- Turbine characteristics, heat rejected vs. LP exhaust pressure, incorporated
- One dimensional model to simulate steam side pressure drop
  
- Objective:
  - Optimum position of ACC relative to turbine house for new project
  - Quantify effect of wind-cross below ACC platform
  - Quantify effect of extended solid walkway around ACC platform
  - Stabilize air flow, and therefore ACC performance, during steady state conditions

# CFD model elements (boiler not shown)


## Detail fan simulation



ACC detail fan simulation  
Fan 2




Eskom detailed fan, 0.5-porosity  
Section plot through center of blade length. Computational ref.





# Static pressure contours for 9 m/s wind


- Wind towards boiler
- 40 m distance from turbine
- Positive pressure above platform due wind interaction with plume
- Negative pressure below platform on leading edge due to high air inlet velocity and flow separation



PROJECT ALPHA : ACC 40m AWAY FROM TURBINE HALL : Easterly wind 9m/s  
Section plot through centre fan row 8 of Unit 4  
All Units running


# Velocity vectors with 9 m/s wind

- Wind towards boiler
- 40 m distance from turbine
- High velocity below the platform resulting in distorted fan inlet flow conditions



PROJECT ALPHA : ACC 40m AWAY FROM TURBINE HALL : Easterly wind 9m/s  
Section plot through centre fan row 8 of Unit 4  
All Units running

# Results of CFD study, 9 m/s wind at 40 m height




# Discussion of CFD results

- **Simulated fan performance predictions compare well with that of supplier but more work is required to validate the model**
- **CFD can be used successfully predict ACC performance, both on air and steam side**
- **Position of ACC platform and shields etc. does have significant effect on performance**
- **A thorough understanding of the air flow about the platform is essential to install appropriate corrective measures**

# Medupi ACC specification

- Minimum distance of 50 m between turbine and boiler
- Solid walkway around ACC platform of minimum width of 2.5 metres
- Wind cross on grade
  - Minimum height equals to a third of platform inlet height
  - Position and porosity determined by CFD study
- Wind shield provided around the platform
- Design air inlet temperature and wind speed based on weather mast measurements at 40 m Above Ground Level
- 15% additional fan motor power is specified
- Solid partitions between each fan
  - Prevent inlet air recirculation when one fan is out of service

# Medupi ACC side view



- Air inlet height = 54 m (177 ft)
- Platform width = 108 m (354 ft)
- 50 m distance from turbine

Side exhaust

Wind cross

Cleaning device


Wind shield

# Medupi ACC

- 6 x 794 MW Output
- Design optimized for range of ambient temperatures
- Average ambient temperature is 23.7°C (74.7°F)
- Back pressure at 23.7 °C is 14.1 kPa (4.2 in Hga)
- Station orientated with prevailing wind direction towards boiler
- **ACC details per unit**
  - 64 fans, 34 ft diameter
  - 8 streets with 8 fans per street


# Cooling system ITD, (Saturated Temp – Ambient Temp.)

ITD vs. ambient temperature






# ITD trend over time



# Ongoing R&D

- Validation of the numerical analysis of axial flow fans
  - Comparison of numerical results with test section results
  - Test in both ideal and distorted inlet flow conditions
- Correlation of fan performance for application in ACC platform simulation
- Determine appropriate fan pressure margin

**Reference:**  
**Stinnes, W.H., von**  
**Backström, T.W**



# Suggestions for further work

- **Performance test code to be re-written**
  - Current code(s) does not recognize for the operational characteristics of an ACC
- **Understanding of axial flow fan performance under distorted conditions**
  - CFD simulations to be validated
  - What is an appropriate fan pressure margin?
- **Ejector sizing**
  - ACC vacuum boundary is orders of magnitude larger than surface condenser and ejector size to be correctly specified
- **Extraction of liquid phase from LP turbine exhaust steam to be considered**
  - Reduction of corrosion on ACC internal surface

# Conclusion

- CFD modeling is an valuable tool to predict ACC performance
  - Approach should be systematic with adequate understanding of sub-components
- ACC performance during windy periods can be improved without need to increase heat transfer area.
- Optimization of ACC should preferably be done before construction starts
- Need for further development work, particularly to validate the axial fan characteristics during distorted inlet flow conditions

# Acknowledgement

- **Continuous support by Prof. DG Kröger is acknowledged**
- **Information and assistance provided by power station personnel**
- **Eskom Management for sponsoring the trip and permission to present the paper**

# References

- Personal discussions with Prof Kröger
- Stinnes, W.H., von Backström, T.W., Effect of cross-flow on the performance of air-cooled heat exchanger fans, Applied Thermal Engineering 22 (2002) 1403-1415.
- Van der Walt, N.T., West, L.A., Sheer, T.J. and Kuball, D., The Design and Operation of a Dry Cooling System for a 200 MW Turbo-generator at Grootvlei Power Station south Africa, The South African Mechanical Engineering, Vol. 26, No. 12, pp.498-511, 1976.
- Ham, A.J., West, L.A., Eskom's Advance into Dry Cooling, VGB Conference, South Africa, Nov 1987.
- Goldshagg, H.B., Lessons Learnt from the Worlds Largest Forced Draft Direct Air Cooled Condenser, Paper presented at the EPRI Int. Symp. On Improved Technology for Fossil power Plants – New and Retrofit Applications, Washington, Marc 1993.
- Goldshagg, H.B., Winds of change at Eskom's Matimba Plant, Modern Power Systems, January 1999.
- Veck, G.A., Rubbers, P.J.E., Economic Evaluation of dry Cooling: The Options, VGB Conference, South Africa, Nov 1987
- Trage, B., Hintzen, F.J., Design and Construction of indirect Dry Cooling Units, VGB Conference, South Africa, Nov 1987
- Duvenhage, K., Du Toit, C.G., Kröger, D.G., Methods to Combat the influence of cross winds on the fan performance in forced draught air-cooled heat exchangers, Proc of the 1st South African Conference on Applied Mechanics (SACAM) 1996, Midrand, South Africa, July 1996.
- Goldshagg, H.B., Vogt, F., du Toit, C.G., Thiart, G.D. and Kröger, D.G., air-cooled Steam Condenser performance in the presence of Cross-winds, EPRI TR-108483 2113, Proceedings: Cooling Tower Technology Conference, pp. 1.61- 1.77, July 1997.
- Kröger, D.G., Air Cooled Heat Exchangers and Cooling Towers, Department of Mechanical Engineering, University of Stellenbosch, 1998.
- K. Zammit, Air Cooled Condenser Design, Specification, and Operation Guidelines, EPRI 1007688
- Phala, S., Aspden, D., du Preez, F., Goldschagg, H., and Northcott, K., "*Corrosion in Air-cooled Condensers – Understanding and Mitigating the Mechanisms*". API Power Chemistry Conference. Sunshine Coast, Queensland, Australia. May 2008. Du Preez, A.F. and D.G. Kröger, Investigation into the Influence of Cross-Winds on the Performance of Dry-Cooling Towers, Proc. 8th Cooling Tower and Spraying Pond Symposium. Karlsruhe, Germany, 1992.
- Du Preez, A.F. and D.G. Kröger, Effect of Wind on Performance of a Dry-Cooling Tower, Heat recovery Systems & CHP, Vol. 13, No. 2, pp. 139-146, 1993
- Du Preez, A.F., Innovative Water Conservation Technology: Dry Cooled Power Stations, Paper presented at the WaterDome World Summit on Sustainable Development, Johannesburg, September 2002.